



HULL

- Color - Oyster gel coat hull with colored inset and waterline [standard color options]
- Structural lamination w/multiple layers of hand laminated fiberglass reinforced plastic using knitted fiberglass
- Stringers - Continuous full length foam cored hand laminated fiberglass structural stringers
- Boarding platform with SS through bolted brackets and under mounted telescopic swim ladder
- Hull Guards - UV-stabilized PVC-guards: anchor, hull and sheer, 316 SS inset on hull side guard
- Fasteners - All exterior fasteners 316 SS
- Bottom Paint - Ablative black antifouling INTERLUX MICRON CSC® (2 coats)
- Port Lights - 7"x14" 316 SS w/screens, hull sides (5)
- Bilge Pumps - 2000 GPH, in three compartments w/auto/manual switches at helm
- Bonding System - common bonding zincs on transom plus rudder, shoe & thruster zincs

DECK

- Color - Oyster gel coat
- Deck - Molded textured surface in walking & work deck areas
- Deck - Raised walk-around side decks
- Door - On transom, hinged
- Scuppers - cockpit
- Anchor Roller Assembly - Polished SS
- Windlass - 12VDC LOFRANS® TIGRES® LW400AN, 1200W anchor windlass w/foot controls at bow and remote control at helm
- Bow Bitt - 316 SS Samson post
- Storage - Cockpit cabinet w/double doors
- Storage - Fender holder recess in cockpit
- Storage - Locking deck hatch to lazarette w/sealing gasket and spring-assist lifts
- Hand Rails - Deck, 1-1/4" bow and stern
- Hand Rails - 1-1/4"x 30" 316 SS on salon cabin top (removable starboard) and ladder on port side
- Ladder - 316 SS open rail w/wide UHMW treads from aft deck to boat deck portside
- Hand Grabs - 316 SS salon roof drains at aft salon corners
- Hand Grabs - 316 SS forward of pilot house doors
- Hand Grab - 316 SS on transom over swim ladder
- Windows - DIAMOND SEA GLAZE® Oyster powder-coated: sixteen windows (five opening w/screens)
- Doors - DIAMOND SEA GLAZE® Oyster powder-coated: two sliding pilot house entry and one aft entry
- Portlights - 10" round 316 SS w/screens and drains in forward cabin (3)
- Cleats - 12" cap rail mounted 316 SS mooring cleats (10)
- Deck Fittings - 316 SS 2" fuel fills (2), SS 1-1/2" water fill, SS 1-1/2" waste suction fitting
- Lighting - Aft deck overhead lights (2)
- Lighting - Boarding platform LED lights (2)
- Outlet - 110VAC GFCI [cockpit]
- Inlet - Phone/TV - dock connection

DECK

- Propane System - (2) 10# aluminum tanks, regulator valve, leak sensor, shut off switch and aft deck sealed tank compartment w/overboard vent
- Pennant Staff - On bow rail
- Sea water deck washdown fore & aft
- Lazarette Vents - SS powder coated louvered vents

PROPULSION / ENGINE ROOM

- Engine - Single 500hp CUMMINS® QSC8.3 electronic
- Marine Reduction Gear - ZF® 304A @ 2.558:1
- Alternator - 160 amp (12V)
- Fuel Filter - RACOR® 75/900MAX dual fuel/water separator filter for main engine
- Exhaust - 8" dual stage water lift muffler transom exit for main engine
- Propeller - 30" HUNG SHEN® 5-blade NiBrAl LH, tuned to class S ISO-484 pitch tolerances
- Propeller Shaft - 2.5" SS w/PSS® drip-less shaft seal
- Seawater Strainers - bronze
- Generator Fuel Filter - RACOR® 120RMAM fuel filter / water separator for primary fuel filter
- Oil Change Pump System - plumbed to main engine, generator and transmission
- Sound Insulation - 1-1/2" w/barrier and silver mylar finish
- Lights - engine room (6)
- Outlet - 110VAC GFCI

HEATING

- Furnace - Diesel ESPAR® Hydronic-10 32,400 BTU

GALLEY

- Range - 3-burner propane stove/oven FORCE-10® 70351
- Microwave Oven - stainless steel finish
- Refrigerator/freezer NOVA KOOL® RFU9000 AC/DC
- Trash Compactor
- Countertop - U-shaped CORIAN® countertop w/covered backsplash and searail, (choice of color)
- Sink - deep double basin polished SS w/single lever spray extension faucet and soap dispenser
- Cabinets - Solid teak face frames w/ teak doors and drawer faces
- Storage - Appliance garage w/ teak tambour roll-up door outboard on forward counter
- Storage - Spice rack over stove w/teak sliding doors
- Storage - Tip-out storage in front of sink
- Drawers - ApplePly®, solid teak faces, full extension ball bearing tracks & sea locks
- Lights - Overhead, 12VDC xenon (4)
- Outlets - 110VAC GFCI protected (2)
- Exhaust fan and switch
- Teak and Holly sole

COMPANIONWAY

- Desk - w/bench seat, file drawer under
- Electrical Panels - AC/DC meters, breakers and gen start, above and outboard of desk area
- Lights- stair, LED
- Light - reading, over desk 12VDC xenon
- Lights - overhead, 12VDC xenon (4)



SALON

- Table - Teak top mounted to a teak wrapped free-standing BENSENZONI® T-248 pedestal
- Cabinet, Ice maker - Teak with U-LINE® BI95
- Teak entertainment center aft port corner w/teak top and includes BOSE® 3.2.1 entertainment sound system with a 19" flat panel TV
- Settee - L-shape w/storage under seating, drop doors converts to berth
- Valances - Teak
- Lights - Stair LED
- Lights - Reading 12VDC (2)
- Lights - Overhead, 12VDC (7)
- Outlets - 110VAC (3)
- Outlet - Phone/TV, in aft port cabinet

PILOT HOUSE

- Helm seat, mounted with adjustable height and slide
- Aft facing seat - forward starboard helm
- Settee w/teak table
- Chart table w/drawer; WILSONART® Graphite laminate counter top
- Teak overhead console and valances
- Engine Control - electronic single lever throttle/shift
- Fuel Gauge - Integrated in SmartCraft VesselView LCD
- Engine Instrumentation - CUMMINS® SmartCraft VesselView LCD
- Bow Thruster Control - joystick
- Compass - RITCHIE® FN-203 flush mount
- Windshield defroster
- Windshield wipers - pantograph style, adjustable speed, self park with washer systems (3)
- Wire for speakers and power for stereo
- Light - chart (red/white)
- Light - reading, 12VDC
- Lights - red LED, over helm (2)
- Outlets - 110VAC (2)
- Power Ports - 12VDC (2)
- 12VDC terminal block for electronics in overhead console
- Hatch - 16.5" w/screen

FORWARD MASTER

- Queen-size berth on center line, storage under
- Mattress - USCG approved hinged pillow top delux coil spring
- Hull side storage cabinets
- Mirror - full length on back of head door
- Drawers under berth (4)
- Lights - reading, 12VDC, over berth (2)
- Lights - overhead, 12VDC, switched (4)
- Outlet - Phone/TV in hanging locker
- Outlets - 110VAC (2)
- Hatch - 22" w/screen
- Chain locker forward w/access door

GUEST CABIN

- Berth - Settee converts to full berth
- Storage Locker - forward inboard corner w/outlet

GUEST CABIN

- Cabinet - hull side storage w/drawers (4)
- Sliding teak entry door
- Lights - overhead, 12VDC (3)
- Lights - reading 12VDC (4)
- Outlets - 110VAC
- Washer/Dryer - vented combination w/hanging locker above

GUEST HEAD

- Toilets - TECMA® EasyFit [household size]
- Shower - stall w/bi-fold door
- Cabinet - vanity w/teak door, SS basin and CORIAN® "Savannah" counter top
- Fixtures - toilet paper holder, towel racks, mirrors
- Floor covering - Linoleum
- Light - overhead dome, 12VDC (2)
- Outlet - 110VAC, GFCI protected
- Exhaust fan w/switch

MASTER HEAD

- Toilets - TECMA® EasyFit [household size]
- Vanity top - CORIAN® "Savannah" w/SS sink, faucet
- Shower - stall w/bi-fold door and faucet, dome light
- Cabinet - vanity w/teak trim and doors
- Linen locker w/teak doors aft bulkhead
- Fixtures - mirrors, toilet paper holder, towel racks (2), towel ring
- Floor covering - Linoleum
- Lights - overhead dome, 12VDC (3)
- Outlet - 110VAC, GFCI protected
- Exhaust fan w/switch

INTERIOR FINISH AND TRIM

- Upholstery - choice of colors [see option sheet/samples]
- Carpet - choice of colors [see option sheet/samples]
- Teak cabinet doors and drawer faces
- Valances, Teak - salon & pilothouse
- Teak interior passageway doors and trim
- CORIAN® - choice of colors [see option sheet/samples]

LAZARETTE

- Fresh water pump - constant pressure
- Water Tank
- Steering gear
- Completely gel coated and ventilated
- Storage space

STEERING SYSTEM

- Steering System - hydraulic
- Rudder and Shoe - SS w/ sacrificial zincs
- Rudder port bearing and shaft lip seal
- Helm Wheel - Teak
- Valves for autopilot hydraulic pump connection
- Bow Thruster - LEWMAR® 185TT 6.0kW 12V 8.0hp @ 213 lb thrust

12V DC ELECTRICAL SYSTEM

- Battery Charger - 40 amp 3-stage
- Batteries, Start - 12V AGM Group-31 (2) w/boxes



12V DC ELECTRICAL SYSTEM

- Batteries, House - 6V AGM deep cycle golf-cart type (6) w/boxes 660 amp hours
- Batteries, Thruster/Windlass - 12V AGM Group-31 (2) w/boxes
- Breaker Panel 12VDC - 36-position w/LED lights
- Master house bank circuit breaker switched at DC Panel
- Battery parallel switch
- Wire - marine grade tinned copper throughout

110V AC ELECTRICAL SYSTEM

- Generator - ONAN® 9kW e-QD Series networked, 110VAC w/sound shield, water lift muffler, water separator exhaust system
- Shore power connections (2), 30 amp, w/50' cords (2)
- Breaker panel - 110VAC w/LED lights
- Switches and outlets - VIMAR® used throughout boat

SAFETY & MOORING PACKAGE

- Fire Extinguishing System - FIREBOY® CG2-500 in engine room w/ auto shut down
- Fire Extinguishers - Class 5-B:C, shipped loose (3)
- High bilge water alarm - Sensor mounted in engine room w/ audible alarm at helm
- Exhaust overheat alarm - Temperature sensor on main engine wet elbow
- Carbon Monoxide detectors in each cabin (2) and in central seating area (1)
- Smoke Detector in each cabin (2) and in central seating area (1)
- Radar reflector
- Horn - Dual electric
- Light - Anchor USCG approved
- Lights - Navigation USCG approved
- Mooring Lines - 5/8" x 25' (4)
- Fenders - G-5 and lines (4)
- NMMA Certification
- Canadian Declaration of Conformity

TANKAGE

- Fuel tanks - 600-gallon in two tanks w/crossover line & sight tube
- Potable Water Tank - 200-gallon w/sight tube
- Gray Water Tank - 20-gallon in keel, with automatic 12V DC pump
- Black Water Tank - 45-gallon in keel, w/deck suction
- Tank Monitoring - Fuel, electronic gauge at helm, and sight tubes on tanks
- Tank Monitoring - Potable water, electric gauge and sight glasses
- Black water monitoring system
- Heater, Water - 11-gallon electric/engine heat

DIMENSIONS

- Length Overall w/optional Bow Pulpit - 46' 3" / 14.10m
- Length Overall - 44' 8" / 13.60m (rigged)
- Beam - 13' 10" / 4.20m
- Draft - 4' 7" / 1.40m
- Freeboard - Amidships, at pilothouse door 4' 11" / 1.50m
- Freeboard - at cockpit 4' 1" / 1.20m

DIMENSIONS

- Height from - Waterline-top to stack top 12' 4" / 3.80m
- Displacement Weight - 31,400 lbs / 14,200kg
- Headroom - Salon 6' 4" / 1.90m
- Headroom - Pilot House 6' 4" / 1.90m
- Headroom - Forward Cabin 6' 10" / 2.10m

COMMISSIONING PACKAGE

- Engine Manual
- Owners Manual - w/Schematics
- Reduction Gear Manual
- Tug Operators Manual
- Fuel filter element for primary RACOR® filters
- Matched gel coat touch-up kit
- Wax Paste - Ultra Performance® 3M9030
- Video - CORIAN® care and maintenance
- Assortment of screws & snap caps
- Multi-Bit Screwdriver & SS Deck Fitting Key
- Clear silicone
- Shaft Seal O-Ring Kit
- Container boxes w/Lids - (2)