



HULL

- Color - Oyster gel coat hull with colored inset and waterline [standard color options]
- Structural lamination w/multiple layers of hand laminated fiberglass reinforced plastic using knitted fiberglass, cored above waterline with ATC Core-cell® closed-cell foam
- Stringers - Continuous full length foam cored hand laminated fiberglass structural stringers
- Bulkheads - Infused using resins & knitted fiberglass reinforcements, cored for structural and sound properties
- Boarding platform integrated in hull w/ telescopic swim ladder
- Hull Guards - UV-stabilized PVC-guards: hull and sheer, 316 SS inset on hull side guard
- Fasteners - All exterior fasteners 316 SS
- Bottom Paint - Ablative black antifouling INTERLUX MICRON CSC® (2 coats)
- Port Lights - 7"x14" 316 SS w/screens, hull sides (3)
- Bilge Pumps - 2200 GPH, in three compartments and one 4000 GPH in engine room w/auto-manual switches at helm
- Bonding System - common bonding zincs on transom plus rudder, shoe & thruster zincs

DECK

- Color - Oyster gel coat
- Deck - Molded textured surface in walking & work deck areas
- Deck - Raised walk-around side decks
- Door - Centerline on transom, hinged
- Drains - cockpit
- Bow Pulpit - Integral part of hull and deck
- Anchor Roller Assembly - Polished SS
- Windlass - 12VDC, LEWMAR® anchor windlass w/foot controls at bow and remote control at helm.
- Bow Bitt - 316 SS Samson post
- Storage - Cockpit cabinet w/double doors
- Storage - Locking deck hatch to lazarette w/sealing gasket and spring-assist lifts
- Hand Rails - Deck, 1-1/4" bow and stern
- Hand Rails - 1-1/4"x 30" 316 SS on salon cabin top (removable starboard) and ladder on port side
- Ladder - 316 SS open rail w/wide UHMW treads from aft deck to boat deck portside
- Hand Grabs - 316 SS salon roof drains at aft salon corners
- Hand Grabs - 316 SS forward of pilot house doors
- Hand Grab - 316 SS on transom over swim ladder
- Windows - DIAMOND SEA GLAZE® Oyster powder coated: 18 total (six opening w/screens)
- Doors - DIAMOND SEA GLAZE® Oyster powder-coated: two sliding pilot house entry, one hatch-style from pilot house to boat deck and one aft entry
- Portlights - 7" x 14" 316 SS w/screens and drains in forward cabin (2)
- Cleats - 12" 316 SS mooring cleats (8), 4 on caprails, 2 aft in each cockpit corner via closed chocks
- Chocks - 316 SS closed chocks, 2 fwd w/horns and 4 aft

DECK

- Deck Fittings - 316 SS 2" fuel fills (2), SS 1-1/2" water fills (2), 1-1/2" waste suction fitting
- Lighting - Aft deck overhead lights (3)
- Lighting - Boarding platform LED lights (2)
- Lighting - Cockpit LED lights
- Outlet - 110VAC GFCI [cockpit]
- Inlet - Phone/TV - dock connection
- Mast - w/radar and antenna mounts
- Pennant Staff - On bow rail
- Sea water deck washdown fore & aft
- Lazarette Vents
- Cockpit shower
- Utility SS basin in aft deck cabinet w/faucet

PROPULSION / ENGINE ROOM

- Engine - Single 610hp CUMMINS® QSM11 electronic
- Marine Reduction Gear - TWIN DISC® MG5095SC 2.46:1 gear
- Alternator - 160 amp (12V)
- Fuel Filter - RACOR® 75/1000MAX duplex fuel filter / water separator for main engine primary fuel filters
- Exhaust - 8" exhaust muffled w/transom discharge
- Propeller - 35" HUNG SHEN® 5-blade NiBrAl LH, tuned to class S ISO-484 pitch tolerances
- Propeller Shaft - 3" SS, AQUAMET® 19 grade or equal, w/ PSS® drip-less shaft seal
- Auxiliary start/stop controls in engine room with analog display
- Stainless steel liquid containment area under engine
- Seawater Strainers - bronze
- Generator Fuel Filter - RACOR® 500MA10 fuel filter / water separator for primary fuel filter
- Potable Water Pump - JOHNSON® Aqua Jet WPS 5.2 12VDC
- Oil Change Pump System - plumbed to main engine, generator and transmission
- Sound Insulation - 1-1/2" w/barrier and silver mylar finish
- Lighting - DC lights (9) fluorescent engine room lights
- Outlet - 110VAC GFCI
- Access to engine room aft via lazarette locking weather tight door
- Access, secondary, to engine room via salon hatch with ladder

HEATING & COOLING

- Heat/cool - Cabins 6,000 BTU MARINE AIR® (2)
- Heat/cool - Salon 12,000 BTU MARINE AIR®
- Heat/cool - Pilothouse 16,000 BTU MARINE AIR®
- Heat/cool - Galley 10,000 BTU MARINE AIR®

GALLEY

- Range - 3-burner electric stove/oven FORCE 10® 75301
- Microwave Oven - GE® JVM1790SK microwave/convection, over cook top w/fan and light
- Refrigerator/freezer - two NOVA KOOL® RFS7501, AC/DC, 15 cuft
- Dishwasher
- Ice maker



GALLEY

- Countertop - U-shaped CORIAN® countertop w/covered backsplash and searail, (choice of color)
- Sink - CORIAN® #850 double sink, w/single lever spray extension faucet and soap dispenser
- Cabinets - Solid teak face frames w/ teak doors and drawer faces
- Storage - Tip-out storage in front of sink
- Drawers - ApplePly®, solid teak faces, full extension ball bearing tracks & sea locks
- Lights - Overhead, switched at aft door & galley 12VDC xenon
- Outlets - 110VAC GFCI protected (3)
- Exhaust fan and switch
- Teak and Holly sole

SALON

- Cabinets - Teak w/doors
- Television - pop-up 26" HD flat panel with BOSE® Lifestyle-28
- Settee - L-shape starboard with built-in table and one chair
- Valances - Teak
- Window Frames - Teak
- Lights - Overhead, switched at aft door & galley
- Lighting – Valance
- Lights - Reading, 12VDC (4)
- Lights - Stair LED
- Outlets - 110VAC (4)
- Outlet - Phone/TV

PILOT HOUSE

- Helm seat - STIDD® 500N Admiral Slimline Low Back, adjustable pedestal
- Settee - U-shaped w/drawer under & teak table
- Overhead console for electronics installation
- Lower teak helm panel tilt up for access to engine instruments and controls
- Raised dash for mounting electronics for two screens
- CORIAN® helm counter w/chart area on port side
- Chart Drawer - large, under chart counter top
- Engine Control - electronic single lever throttle/shift
- Engine Instrumentation - CUMMINS® SmartCraft VesselView LCD
- Compass - RITCHIE® FN-203 flush mount
- Windshield wipers – (3) pantograph style, adjustable speed, self park with washer system
- Windshield defroster
- Lights - overhead, switched at two locations
- Lights - overhead, 12VDC red LED (2)
- Lights - Reading, 12VDC (2)
- Light - chart (red/white)
- Outlets- 110VAC (3)
- Power Ports - 12VDC (2)
- Outlet - Phone/TV
- 12VDC electrical panel
- Direct access to boat deck via stairway
- Window Frames - Teak

FORWARD GUEST

- Mattress - USCG approved hinged pillow top delux coil spring
- Full size berth w/storage under
- Hanging locker w/automatic lighting and cedar lining
- Teak faced cabinets w/teak drawer faces and doors
- Direct access to guest head
- Teak entry door
- Xenon overhead lights
- Lights - Reading, 12VDC (2)
- Outlets - 110VAC (2)
- Outlet - Phone/TV
- Washer/Dryer - vented combination unit

MID MASTER

- Queen-size berth w/storage under
- Mattress - USCG approved hinged pillow top delux coil spring
- Teak faced cabinets w/ teak drawer faces and doors
- Hanging locker w/shelf, automatic lighting, cedar lining
- Audio - MAGNOLIA designed system w/two speakers
- Teak sliding entry door
- Direct access to master head
- Lights - overhead, switched at door
- Lights - Reading, 12VDC (2)
- Outlet - Phone/TV
- Outlets - 110VAC (3)

HEAD COMPARTMENTS

- Toilets - TECMA® EasyFit [household size]
- Shower w/textured shower sole & glass door
- Teak cabinets w/CORIAN® "Savannah" top & SS basin
- Vanity w/lighting, storage and mirrored doors
- Toilet paper holders, towel racks, and mirrors
- Teak entry doors w/full mirror, w/locking handle
- Teak & Holly floor covering
- Lights - overhead
- Outlet - 110VAC
- Exhaust fan w/switch

INTERIOR FINISH AND TRIM

- Upholstery - choice of colors [see option sheet/samples]
- Carpet - choice of colors [see option sheet/samples]
- Teak interior passageway doors and trim
- Teak cabinet doors and drawer faces
- Valances, Teak - salon & pilothouse
- Wall Covering - Teak wainscot, vinyl overhead & upper walls
- CORIAN® - choice of colors [see option sheet/samples]
- Central Vacuum System - two inlets

LAZARETTE

- Access to engine room via DIAMOND SEA-GLAZE® locking weather tight door
- Compartment is lighted, ventilated and fully gel coated
- Steering gear
- Completely gel coated and ventilated
- Storage space



LAZARETTE

- Outlet - 110VAC

STEERING SYSTEM

- Steering System - hydraulic
- Autopilot hydraulic pump
- Rudder port bearing and shaft lip seal
- Rudder - stainless steel foil shape rudder
- Cast iron double tiller arm w/rudder stops
- Helm Wheel - Teak
- Bow Thruster - SIDE POWER® SE130/250T 6.5kW 12V 8.7hp @ 350 lb thrust
- Stern Thruster - SIDE POWER® SE100/185T 12V 8.4hp @ 256 lb thrust

12V DC ELECTRICAL SYSTEM

- Battery Charger - 40 amp 3-stage
- Batteries, Start - 12V AGM Group-31 (3) w/boxes
- Batteries, House - 6V AGM deep cycle golf-cart type (6) w/boxes 660 amp hours
- Battery, Generator - 12V AGM Group-27
- Breaker Panel - 12VDC w/LED lights
- Master on/off switches for engine and house batteries
- Battery parallel switch
- Wire - marine grade tinned copper throughout

110/220V AC ELECTRICAL SYSTEM

- Shore power inlet connections - 50A / 110VAC / 220VAC one inlet port side aft of pilot house door and one inlet in cockpit on starboard side.
- Generator - ONAN® 11.5kW e-QD 110/220VAC w/sound shield, water lift muffler, water separator exhaust system
- Inverter - 2500 watt modified sinewave with remote control panel
- Shorepower Cordset - 50' 220V AC 50 amp
- Breaker panels - AC w/LED status lights
- Switches and outlets - VIMAR® used throughout boat

SAFETY & MOORING PACKAGE

- Fire Extinguishing System - FIREBOY® MA2-900 in engine room w/ auto shut down
- Fire Extinguishers - Class 5-B:C, shipped loose (4)
- High bilge water alarm - Sensor mounted in engine room w/ audible alarm at helm
- Exhaust overheat alarm - Temperature sensor on main engine wet elbow
- Carbon Monoxide detectors in each cabin (2) and in central seating area (1)
- Smoke Detector in each cabin (2) and in central seating area (1)
- Radar reflector
- Horn - Air
- Light - Anchor USCG approved
- Lights - Navigation USCG approved
- Mooring Lines - 5/8" x 35' (4)
- Fenders - G-6 and lines (4)
- Prewired for closed circuit camera - Aft deck and Engine Room
- NMMA Certification
- Canadian Declaration of Conformity

TANKAGE

- Fuel tanks - Aluminum, located in engine room 800-gallon capacity in 2 tanks w/valves, sight gauges and crossover line w/shutoff valves and electric monitoring
- Water Tanks - 300-gallon capacity in 2 tanks w/valves sight gauges and crossover line aluminum, located in engine room
- Grey Water Tank - 60 gallon capacity poly w/automatic discharge pump or manual on/off for holding tank
- Black Water Tank - 60+ gallon capacity FRP construction in keel, w/deck suction & macerator w/overboard discharge.
- Tank Monitoring - Fuel, electronic gauge at helm, and sight tubes on tanks
- Tank Monitoring - Potable water, electric gauge and sight glasses
- Black water monitoring system
- Heater, Water - 20-gallon electric/engine heat

DIMENSIONS

- Length Overall - 52' 8" / 16.10m (rigged)
- Length @ WL - 48' 4" / 14.70m
- Beam - 16' 1" / 4.90m
- Draft - 3' 11" / 1.20m
- Freeboard - midships 5' 6" / 1.70m
- Freeboard - cockpit 5' 4" / 1.60m
- Approximate heights from: waterline to top of mast light 20' 11" / 6.4m
- Approximate heights from: Waterline-flybridge, mast down 17' 4" / 5.30m
- Displacement Weight - 45,000 lbs. / 20,455kg
- Headroom - Forward Cabin 6' 8" / 2.0m
- Headroom - Engine Room 4' 8" / 1.4m
- Headroom - Mid Cabins 6' 5" / 2.0m
- Headroom - Salon & Galley 6' 5" / 2.0m
- Headroom - Pilot House 6' 10" / 2.1m

COMMISSIONING PACKAGE

- Engine Manual
- Owners Manual - w/Schematics
- Reduction Gear Manual
- Tug Operators Manual
- Fuel filter element for primary RACOR® filters
- Matched gel coat touch-up kit
- Wax Paste - Ultra Performance® 3M9030
- Video - CORIAN® care and maintenance
- Assortment of screws & snap caps
- Multi-Bit Screwdriver & SS Deck Fitting Key
- Clear silicone
- Shaft Seal O-Ring Kit
- Container boxes w/Lids - (2)
- Vacuum accessories kit